

wp theme auto-updates status

wp

- wp
- wp
- [GLOBAL PARAMETERS](#)

wp

wp

wp wp

[<theme>...] : wp

[--all] : wp

[--enabled-only] : wp

[--disabled-only] : wp

[--field=<field>] : wp

[--format=<format>] : wp --- wp : table wp :

- table
- csv
- json
- yaml
- count ---

wp

```
# 確認テーマの更新状況
$ wp theme auto-updates status twentyseven

+-----+-----+
| name           | status   |
+-----+-----+
| twentyseven    | disabled |
+-----+-----+

# テーマの更新を有効にする
$ wp theme auto-updates status --all --enabled-only --field=name
twentyseven
twentyseven
```

GLOBAL PARAMETERS

These [global parameters](#) have the same behavior across all commands and affect how WP-CLI interacts with WordPress.

Argument	Description
<code>--path=<path></code>	Path to the WordPress files.
<code>--url=<url></code>	Pretend request came from given URL. In multisite, this argument is how the target site is specified.
<code>--ssh=[<scheme>:][<user>@]<host container>[:<port>][<path>]</code>	Perform operation against a remote server over SSH (or a container using scheme of "docker", "docker-compose", "docker-compose-run", "vagrant").
<code>--http=<http></code>	Perform operation against a remote WordPress installation over HTTP.
<code>--user=<id login email></code>	Set the WordPress user.
<code>--skip-plugins[=<plugins>]</code>	Skip loading all plugins, or a comma-separated list of plugins. Note: mu-plugins are still loaded.
<code>--skip-themes[=<themes>]</code>	Skip loading all themes, or a comma-separated list of themes.
<code>--skip-packages</code>	Skip loading all installed packages.
<code>--require=<path></code>	Load PHP file before running the command (may be used more than once).
<code>--exec=<php-code></code>	Execute PHP code before running the command (may be used more than once).
<code>--context=<context></code>	Load WordPress in a given context.
<code>--[no-]color</code>	Whether to colorize the output.

Argument	Description
<code>--debug[=<group>]</code>	Show all PHP errors and add verbosity to WP-CLI output. Built-in groups include: bootstrap, commandfactory, and help.
<code>--prompt[=<assoc>]</code>	Prompt the user to enter values for all command arguments, or a subset specified as comma-separated values.
<code>--quiet</code>	Suppress informational messages.

#2

2026-03-26 17:08:46 UTC

2026-03-26 17:08:46 UTC