wp theme mod get

□□

- □□
- □□
- GLOBAL PARAMETERS

□□□□□□□□□□□□□□□□

□□

□□□□□□□□□□□□□□□□□□ □□□□ □□□□□

[<mod>...] : □□□□□□□□□□□□□□□□

[--field=<field>] : □□□□□□□□□

[--all] : □□□□□□□□□□□□

[--format=<format>] : □□□□□□□□□□ --- □□□ : table □□ :

- table
- json
- csv
- yaml ---

□□

```
# □□□□□□□□□□□
$ wp theme mod get --all
+------------------+---------+
| key              | value   |
+------------------+---------+
| background_color | dd3333  |
| link_color       | #dd9933 |
```

```
| main_text_color  | #8224e3 |
+------------------+---------+

# □ JSON □□□□□□□□□□□□□
$ wp theme mod get background_color --format=json
[{"key":"background_color","value":"dd3333"}]

# □□□□□□□□□□□□□
$ wp theme mod get background_color --field=value
dd3333

# □□□□□□□□□□□
$ wp theme mod get background_color header_textcolor
+------------------+--------+
| key              | value  |
+------------------+--------+
| background_color | dd3333 |
| header_textcolor |        |
+------------------+--------+
```

GLOBAL PARAMETERS

These global parameters have the same behavior across all commands and affect how WP-CLI interacts with WordPress.

Argument	Description
`--path=<path>`	Path to the WordPress files.
`--url=<url>`	Pretend request came from given URL. In multisite, this argument is how the target site is specified.
`--ssh=[<scheme>:][<user>@]<host|container>[:<port>][<path>]`	Perform operation against a remote server over SSH (or a container using scheme of "docker", "docker-compose", "docker-compose-run", "vagrant").
`--http=<http>`	Perform operation against a remote WordPress installation over HTTP.
`--user=<id|login|email>`	Set the WordPress user.
`--skip-plugins[=<plugins>]`	Skip loading all plugins, or a comma-separated list of plugins. Note: mu-plugins are still loaded.
`--skip-themes[=<themes>]`	Skip loading all themes, or a comma-separated list of themes.
`--skip-packages`	Skip loading all installed packages.

Argument	Description
`--require=<path>`	Load PHP file before running the command (may be used more than once).
`--exec=<php-code>`	Execute PHP code before running the command (may be used more than once).
`--context=<context>`	Load WordPress in a given context.
`--[no-]color`	Whether to colorize the output.
`--debug[=<group>]`	Show all PHP errors and add verbosity to WP-CLI output. Built-in groups include: bootstrap, commandfactory, and help.
`--prompt[=<assoc>]`	Prompt the user to enter values for all command arguments, or a subset specified as comma-separated values.
`--quiet`	Suppress informational messages.

□□□ #2
□ □□□ □□□ 2026-03-26 17:08:46 UTC
□ □□□ □□□ 2026-03-26 17:08:46 UTC