wp transient list

目录
选项
可用字段
示例
GLOBAL PARAMETERS

列出瞬态数据及其值。

选项

有关所用语法约定的详细说明，请参阅 参数语法 参考文档。

[--search=<pattern>] : 使用通配符（ * 和 ? ）来匹配瞬态数据名称。

[--exclude=<pattern>] : 要排除的模式。使用通配符（ * 和 ? ）来匹配瞬态数据名称。

[--network] : 获取网络 |
站点瞬态数据的值。在单站点上，这是一个特殊命名的缓存键。在多站点上，这是一个全局缓存（而不是站点
本地的）。

[--unserialize] : 在输出中反序列化瞬态数据值。

[--human-readable] : 以人类可读的格式输出过期时间。

[--fields=<fields>] : 将输出限制为特定的对象字段。

[--format=<format>] : 值的序列化格式。 --- 默认值: table 选项:

table
json

csv
count

yaml ---

可用字段

□□□□□□□□□□□□□□□□□□□

- name
- value
- expiration

□□

```
# □□□□□□□□□
$ wp transient list
 +------+-------+---------------+
 | name | value | expiration    |
 +------+-------+---------------+
 | foo  | bar   | 39 □□□     |
 | foo2 | bar2  | □□□□       |
 | foo3 | bar2  | □□□         |
 | foo4 | bar4  | 4 □□□      |
 +------+-------+---------------+
```

GLOBAL PARAMETERS

These global parameters have the same behavior across all commands and affect how WP-CLI interacts with WordPress.

Argument	Description
`--path=<path>`	Path to the WordPress files.
`--url=<url>`	Pretend request came from given URL. In multisite, this argument is how the target site is specified.
`--ssh=[<scheme>:][<user>@]<host|container>[:<port>][<path>]`	Perform operation against a remote server over SSH (or a container using scheme of "docker", "docker-compose", "docker-compose-run", "vagrant").
`--http=<http>`	Perform operation against a remote WordPress installation over HTTP.
`--user=<id|login|email>`	Set the WordPress user.
`--skip-plugins[=<plugins>]`	Skip loading all plugins, or a comma-separated list of plugins. Note: mu-plugins are still loaded.
`--skip-themes[=<themes>]`	Skip loading all themes, or a comma-separated list of themes.
`--skip-packages`	Skip loading all installed packages.

Argument	Description
`--require=<path>`	Load PHP file before running the command (may be used more than once).
`--exec=<php-code>`	Execute PHP code before running the command (may be used more than once).
`--context=<context>`	Load WordPress in a given context.
`--[no-]color`	Whether to colorize the output.
`--debug[=<group>]`	Show all PHP errors and add verbosity to WP-CLI output. Built-in groups include: bootstrap, commandfactory, and help.
`--prompt[=<assoc>]`	Prompt the user to enter values for all command arguments, or a subset specified as comma-separated values.
`--quiet`	Suppress informational messages.

□□□ #2
□ □□□ □□□ 2026-03-26 17:08:46 UTC
□ □□□ □□□ 2026-03-26 17:08:46 UTC