

wp user update

11

- II
- EXAMPLES
- GLOBAL PARAMETERS

--	--



<user>... : ID

```
[--user_pass=<password>] : 
```

```
[--user_nicename=<nice_name>]:  URL 
```

```
[--user_url=<url>] : □□□□□ URL □□□□
```

```
[--user email=<email>] : 
```

```
[--display_name=<display name>]:
```

```
[--nickname=<nickname>] : [ ][ ][ ][ ][ ][ ][ ][ ][ ][ ]
```

```
[--first name=<first name>] : 
```

```
[--last_name=<last_name>] : 
```

```
[--description=<description>) : [ ]
```

```
[--rich_editing=<rich_editing>]:
```

```
[--user registered=<yyyy-mm-dd-hh-ii-ss>] : 
```

```
[--role=<role>] : 
```

--<field>=<value> :

wp_update_user()

[--skip-email] :

EXAMPLES

```
# Update user
$ wp user update 123 --display_name=Mary --user_pass=marypass
Success: Updated user 123.
```

GLOBAL PARAMETERS

These [global parameters](#) have the same behavior across all commands and affect how WP-CLI interacts with WordPress.

Argument	Description
<code>--path=<path></code>	Path to the WordPress files.
<code>--url=<url></code>	Pretend request came from given URL. In multisite, this argument is how the target site is specified.
<code>--ssh=[<scheme>:][<user>@]<host container>[:<port>][<path>]</code>	Perform operation against a remote server over SSH (or a container using scheme of "docker", "docker-compose", "docker-compose-run", "vagrant").
<code>--http=<http></code>	Perform operation against a remote WordPress installation over HTTP.
<code>--user=<id login email></code>	Set the WordPress user.
<code>--skip-plugins[=<plugins>]</code>	Skip loading all plugins, or a comma-separated list of plugins. Note: mu-plugins are still loaded.
<code>--skip-themes[=<themes>]</code>	Skip loading all themes, or a comma-separated list of themes.
<code>--skip-packages</code>	Skip loading all installed packages.
<code>--require=<path></code>	Load PHP file before running the command (may be used more than once).
<code>--exec=<php-code></code>	Execute PHP code before running the command (may be used more than once).
<code>--context=<context></code>	Load WordPress in a given context.
<code>--[no-]color</code>	Whether to colorize the output.
<code>--debug[=<group>]</code>	Show all PHP errors and add verbosity to WP-CLI output. Built-in groups include: bootstrap, commandfactory, and help.

Argument	Description
--prompt[=<assoc>]	Prompt the user to enter values for all command arguments, or a subset specified as comma-separated values.
--quiet	Suppress informational messages.

#2

2026-03-26 17:08:46 UTC

2026-03-26 17:08:46 UTC