

Given /[^]a downloaded Phar with (?:the same version|version "([[^]";]+)");\$ /



- [Usage](#)
- [Related](#)

Download a specific WP-CLI Phar version from GitHub.

Usage

Scenario: My example scenario

Given an empty directory

And a downloaded Phar with version "2.11.0"

Scenario: My other scenario

Given an empty directory

And a downloaded Phar with the same version

Behat steps documentation is generated from the WP-CLI codebase on every release. To suggest improvements, please submit a pull request.

Related

- [**Given an empty directory**](#) - Creates an empty directory.
- [**Given /^an? \(empty|non-existent\) \(\[^\s\]+\) directory\\$/**](#) - Creates or deletes a specific directory.
- [**Given an empty cache**](#) - Clears the WP-CLI cache directory.
- [**Given /^an? \("^\[^"\]*"|"\[^"\]*"|'\[^'\]*'|'\[^\s\]*'\) \(file|cache file\):\\$/**](#) - Creates a file with the given contents.
- [**Given /^"\(\[^\"\]*\)" replaced with "\(\[^\"\]*\)" in the \(\[^\s\]+\) file\\$/**](#) - Search and replace a string in a file using regex.
- [**Given /^that HTTP requests to \(.*\) will respond with:\\$/**](#) - Mock HTTP requests to a given URL.
- [**Given WP files**](#) - Download WordPress files without installing.
- [**Given wp-config.php**](#) - Create a wp-config.php file using `wp config create`.
- [**Given a database**](#) - Creates an empty database.
- [**Given /^a WP\(\d+\)? install\(?:ation\)?\\$/**](#) - Installs WordPress.
- [**Given /^a WP\(\[^\s\]+\)? install\(?:ation\)? in '\(\[^\s\]*\)'\\$/**](#) - Installs WordPress in a given directory.
- [**Given a WP install\(ation\) with Composer**](#) - Installs WordPress with Composer.
- [**Given a WP install\(ation\) with Composer and a custom vendor directory :vendor_directory**](#) - Installs WordPress with Composer and a custom vendor directory.
- [**Given /^a WP multisite \(subdirectory|subdomain\)?s?\(install|installation\)\\$/**](#) - Installs WordPress Multisite.
- [**Given these installed and active plugins:**](#) - Installs and activates one or more plugins.
- [**Given a custom wp-content directory**](#) - Configure a custom `wp-content` directory.
- [**Given download:**](#) - Download multiple files into the given destinations.
- [**Given /^save \(STDOUT|STDERR\) \(\[\'.\]+\^\[^\'\]*\)?s?as \{\(\w+\)\}\\$/**](#) - Store STDOUT or STDERR contents in a variable.
- [**Given /^a new Phar with \(?:the same version|version "\(\[^\"\]+\)"\)\\$/**](#) - Build a new WP-CLI Phar file with a given version.
- [**Given /^save the \(.+\) file \(\[\'.\]+\^\[^\'\]*\)?as \{\(\w+\)\}\\$/**](#) - Stores the contents of the given file in a variable.
- [**Given a misconfigured WP_CONTENT_DIR constant directory**](#) - Modify wp-config.php to set `WP\_CONTENT\_DIR` to an empty string.
- [**Given a dependency on current wp-cli**](#) - Add `wp-cli/wp-cli` as a Composer dependency.

- [Given a PHP built-in web server](#) - Start a PHP built-in web server in the current directory.
 - [Given a PHP built-in web server to serve :subdir](#) - Start a PHP built-in web server in the given subdirectory.
-

📁 #2

📁 cocobook-sync 📁 2025-06-25 18:05:32 UTC

📁 cocobook-sync 📁 2026-10-06 21:11:26 UTC