

Given /^a WP multisite (subdirectory|subdomain)?\s?(install|installation)\$/



- [Usage](#)
 - [Related](#)
-

Installs WordPress Multisite.

Usage

Supports either subdirectory or subdomain installation.

Scenario: My example scenario

Given a WP multisite subdomain installation

...

Scenario: My other scenario

Given a WP subdirectory install

...

Behat steps documentation is generated from the WP-CLI codebase on every release. To suggest improvements, please submit a pull request.

Related

- [Given an empty directory](#) - Creates an empty directory.

- **Given /^an? (empty|non-existent) ([^\s]+) directory\$/** - Creates or deletes a specific directory.
 - **Given an empty cache** - Clears the WP-CLI cache directory.
 - **Given /^an? ("^[^"]+"|"[^\s]+") (file|cache file):\$/** - Creates a file with the given contents.
 - **Given /^"([^\"]+) " replaced with "([^\"]+)" in the ([^\s]+) file\$/** - Search and replace a string in a file using regex.
 - **Given /^that HTTP requests to (.*) will respond with:\$/** - Mock HTTP requests to a given URL.
 - **Given WP files** - Download WordPress files without installing.
 - **Given wp-config.php** - Create a wp-config.php file using `wp config create`.
 - **Given a database** - Creates an empty database.
 - **Given /^a WP(\d[^\s]+)? install(?::action)?\$/** - Installs WordPress.
 - **Given /^a WP([^\s]+)? install(?::action)? in ["']?([^\"]+|'')?["']?\$/** - Installs WordPress in a given directory.
 - **Given a WP install(action) with Composer** - Installs WordPress with Composer.
 - **Given a WP install(action) with Composer and a custom vendor directory :vendor_directory** - Installs WordPress with Composer and a custom vendor directory.
 - **Given these installed and active plugins:** - Installs and activates one or more plugins.
 - **Given a custom wp-content directory** - Configure a custom `wp-content` directory.
 - **Given download:** - Download multiple files into the given destinations.
 - **Given /^save (STDOUT|STDERR) ([\'].+[^\'])?s?as \{(\w+)\}\$/** - Store STDOUT or STDERR contents in a variable.
 - **Given /^a new Phar with (?:the same version|version "([^\"]+)")\$/** - Build a new WP-CLI Phar file with a given version.
 - **Given /^a downloaded Phar with (?:the same version|version "([^\"]+)")\$/** - Download a specific WP-CLI Phar version from GitHub.
 - **Given /^save the (.+) file ([\'].+[^\'])?as \{(\w+)\}\$/** - Stores the contents of the given file in a variable.
 - **Given a misconfigured WP_CONTENT_DIR constant directory** - Modify wp-config.php to set `WP\_CONTENT\_DIR` to an empty string.
 - **Given a dependency on current wp-cli** - Add `wp-cli/wp-cli` as a Composer dependency.
 - **Given a PHP built-in web server** - Start a PHP built-in web server in the current directory.
 - **Given a PHP built-in web server to serve :subdir** - Start a PHP built-in web server in the given subdirectory.
-

#2

cocobook-sync 2026-10-28 11:01:35 UTC

cocobook-sync 2026-10-28 11:34:39 UTC