

Given download:



- [Usage](#)
 - [Related](#)
-

Download multiple files into the given destinations.

Usage

Scenario: My example scenario

Given download:

path	url	
{CACHE_DIR}/foo.jpg	https://example.com/foo.jpg	
{CACHE_DIR}/bar.png	https://example.com/another-image.png	

Behat steps documentation is generated from the WP-CLI codebase on every release. To suggest improvements, please submit a pull request.

Related

- [Given an empty directory](#) - Creates an empty directory.
- [Given /^an? \(empty|non-existent\) \(\[^\s\]+\) directory\\$/](#) - Creates or deletes a specific directory.
- [Given an empty cache](#) - Clears the WP-CLI cache directory.
- [Given /^an? \("\[^"\]+"|"\[^s\]+\) \(file|cache file\):\\$/](#) - Creates a file with the given contents.
- [Given /^"\(\[^\"\]+\)" replaced with "\(\[^\"\]+\)" in the \(\[^\s\]+\) file\\$/](#) - Search and replace a string in a file using regex.
- [Given /^that HTTP requests to \(.*\) will respond with:\\$/](#) - Mock HTTP requests to a given URL.

- [**Given WP files**](#) - Download WordPress files without installing.
- [**Given wp-config.php**](#) - Create a wp-config.php file using `wp config create`.
- [**Given a database**](#) - Creates an empty database.
- [**Given /^a WP\(\d\[^\s\]+\)? install\(?:ation\)?\\$/**](#) - Installs WordPress.
- [**Given /^a WP\(\[^\s\]+\)? install\(?:ation\)? in \["\]?\(\[^\"\]+\)\["\]?\\$/**](#) - Installs WordPress in a given directory.
- [**Given a WP install\(ation\) with Composer**](#) - Installs WordPress with Composer.
- [**Given a WP install\(ation\) with Composer and a custom vendor directory :vendor_directory**](#) - Installs WordPress with Composer and a custom vendor directory.
- [**Given /^a WP multisite \(subdirectory|subdomain\)?\s?\(install|installation\)\\$/**](#) - Installs WordPress Multisite.
- [**Given these installed and active plugins:**](#) - Installs and activates one or more plugins.
- [**Given a custom wp-content directory**](#) - Configure a custom `wp-content` directory.
- [**Given /^save \(STDOUT|STDERR\) \(\[\'.\]+\^\[^\'\]\)*\s?as \{\(\w+\)\}\\$/**](#) - Store STDOUT or STDERR contents in a variable.
- [**Given /^a new Phar with \(?:the same version|version "\(\[^\"\]+\)"\\$\)/**](#) - Build a new WP-CLI Phar file with a given version.
- [**Given /^a downloaded Phar with \(?:the same version|version "\(\[^\"\]+\)"\\$\)/**](#) - Download a specific WP-CLI Phar version from GitHub.
- [**Given /^save the \(.+\) file \(\[\'.\]+\^\[^\'\]\)*\s?as \{\(\w+\)\}\\$/**](#) - Stores the contents of the given file in a variable.
- [**Given a misconfigured WP_CONTENT_DIR constant directory**](#) - Modify wp-config.php to set `WP\_CONTENT\_DIR` to an empty string.
- [**Given a dependency on current wp-cli**](#) - Add `wp-cli/wp-cli` as a Composer dependency.
- [**Given a PHP built-in web server**](#) - Start a PHP built-in web server in the current directory.
- [**Given a PHP built-in web server to serve :subdir**](#) - Start a PHP built-in web server in the given subdirectory.

📄 #2

📄 cocobook-sync 📄 2026-10-28 11:01:58 UTC

📄 cocobook-sync 📄 2026-10-28 11:37:37 UTC