

Given /^that HTTP requests to (.*)? will respond with:\$/



- [Usage](#)
 - [Related](#)
-

Mock HTTP requests to a given URL.

Usage

Scenario: My example scenario

Given that HTTP requests to `https://api.github.com/repos/wp-cli/wp-cli/releases?per_page=100` will respond with:

```
"""
```

```
HTTP/1.1 200
```

```
Content-Type: application/json
```

```
{ "foo": "bar" }
```

```
"""
```

Behat steps documentation is generated from the WP-CLI codebase on every release. To suggest improvements, please submit a pull request.

Related

- [Given an empty directory](#) - Creates an empty directory.
- [Given /^an? \(empty|non-existent\) \(\[^\s\]+\) directory\\$/](#) - Creates or deletes a specific directory.

- **Given an empty cache** - Clears the WP-CLI cache directory.
- **Given / ^an? ("[^"]+"|"[^s]+) (file|cache file):\$/** - Creates a file with the given contents.
- **Given / ^"([^\"]+) " replaced with "([^\"]+)" in the ([^\s]+) file\$/** - Search and replace a string in a file using regex.
- **Given WP files** - Download WordPress files without installing.
- **Given wp-config.php** - Create a wp-config.php file using `wp config create`.
- **Given a database** - Creates an empty database.
- **Given / ^a WP(\d[^\s]+)? install(?::action)?\$/** - Installs WordPress.
- **Given / ^a WP([^\s]+)? install(?::action)? in ["']?([^\"]+|'')?["']?\$/** - Installs WordPress in a given directory.
- **Given a WP install(action) with Composer** - Installs WordPress with Composer.
- **Given a WP install(action) with Composer and a custom vendor directory :vendor_directory** - Installs WordPress with Composer and a custom vendor directory.
- **Given / ^a WP multisite (subdirectory|subdomain)?\s?(install|installation)\$/** - Installs WordPress Multisite.
- **Given these installed and active plugins:** - Installs and activates one or more plugins.
- **Given a custom wp-content directory** - Configure a custom `wp-content` directory.
- **Given download:** - Download multiple files into the given destinations.
- **Given / ^save (STDOUT|STDERR) ([\'.]+[^\'])?\s?as \{(\w+)\}\\$/** - Store STDOUT or STDERR contents in a variable.
- **Given / ^a new Phar with (?:the same version|version "([^\"]+)")\$/** - Build a new WP-CLI Phar file with a given version.
- **Given / ^a downloaded Phar with (?:the same version|version "([^\"]+)")\$/** - Download a specific WP-CLI Phar version from GitHub.
- **Given / ^save the (.+) file ([\'.]+[^\'])?\s?as \{(\w+)\}\\$/** - Stores the contents of the given file in a variable.
- **Given a misconfigured WP_CONTENT_DIR constant directory** - Modify wp-config.php to set `WP\_CONTENT\_DIR` to an empty string.
- **Given a dependency on current wp-cli** - Add `wp-cli/wp-cli` as a Composer dependency.
- **Given a PHP built-in web server** - Start a PHP built-in web server in the current directory.
- **Given a PHP built-in web server to serve :subdir** - Start a PHP built-in web server in the given subdirectory.