

Then /^STDOUT should end with a table containing rows:\$/



- [Usage](#)
- [Related](#)

Expect STDOUT to end with a table containing the given rows.

Usage

Useful when the table is preceded by some other output.

Scenario: My example scenario

Given a WP installation

When I run `wp search-replace foo bar --report-changed-only`

Then STDOUT should contain:

"""

Success: Made 3 replacements.

"""

And STDOUT should end with a table containing rows:

Table	Column	Replacements	Type
wp_options	option_value	1	PHP
wp_postmeta	meta_value	1	SQL
wp_posts	post_title	1	SQL

Behat steps documentation is generated from the WP-CLI codebase on every release. To suggest improvements, please submit a pull request.

Related

- [**Then /^the return code should\(not\)? be \(\d+\)\\$/**](#) - Expect a specific exit code of the previous command.
 - [**Then /^\(STDOUT|STDERR\) should\(strictly\)? \(be|contain|not contain\):\\$/**](#) - Check the contents of STDOUT or STDERR.
 - [**Then /^\(STDOUT|STDERR\) should be a number\\$/**](#) - Expect STDOUT or STDERR to be a numeric value.
 - [**Then /^\(STDOUT|STDERR\) should not be a number\\$/**](#) - Expect STDOUT or STDERR to not be a numeric value.
 - [**Then /^STDOUT should be a table containing rows:\\$/**](#) - Expect STDOUT to be a table containing the given rows.
 - [**Then /^STDOUT should be JSON containing:\\$/**](#) - Expect valid JSON output in STDOUT.
 - [**Then /^STDOUT should be a JSON array containing:\\$/**](#) - Expect valid JSON array output in STDOUT.
 - [**Then /^STDOUT should be CSV containing:\\$/**](#) - Expect STDOUT to be CSV containing certain values.
 - [**Then /^STDOUT should be YAML containing:\\$/**](#) - Expect STDOUT to be YAML containing certain content.
 - [**Then /^\(STDOUT|STDERR\) should be empty\\$/**](#) - Expect STDOUT or STDERR to be empty.
 - [**Then /^\(STDOUT|STDERR\) should not be empty\\$/**](#) - Expect STDOUT or STDERR not to be empty.
 - [**Then /^\(STDOUT|STDERR\) should be a version string \(<|<=|>|>=|==|!=|<>\)\(\[+\w.{}-\]+\)\\$/**](#) - Expect STDOUT or STDERR to be a version string comparing to the given version.
 - [**Then /^the \(.+\) \(file|directory\) should\(strictly\)? \(exist|not exist|be:|contain:|not contain:\)\\$/**](#) - Expect a certain file or directory to (not) exist or (not) contain certain contents.
 - [**Then /^the contents of the \(.+\) file should\(not\)? match \(\(\(\V.+V\)|\(#.+#\)\)\(\[a-z\]+\)?\)/**](#) - Match file contents against a regex.
 - [**Then /^\(STDOUT|STDERR\) should\(not\)? match \(\(\(\V.+V\)|\(#.+#\)\)\(\[a-z\]+\)?\)/**](#) - Match STDOUT or STDERR against a regex.
 - [**Then /^an email should \(be sent|not be sent\)\\$/**](#) - Expect an email to be sent (or not).
 - [**Then the HTTP status code should be :code**](#) - Expect the HTTP status code for visiting `http://localhost:8080`.
-

#1

cocobook-sync ## 2026-10-28 11:38:10 UTC

cocobook-sync ## 2026-10-28 11:38:10 UTC