Then /^the contents of the (.+) file should(not)? match (((\/.+\/)|(#.+#))([a-z]+)?)$/

- Usage
- Related

Match file contents against a regex.

Usage

```
Scenario: My example scenario
  When I run `wp scaffold plugin hello-world`
  Then the contents of the wp-content/plugins/hello-world/languages/hello-world.pot file
should match /X-Generator:\s/
```

Behat steps documentation is generated from the WP-CLI codebase on every release. To suggest improvements, please submit a pull request.

Related

- **Then /^the return code should(not)? be (\d+)$/** - Expect a specific exit code of the previous command.
- **Then /^(STDOUT|STDERR) should(strictly)? (be|contain|not contain):$/** - Check the contents of STDOUT or STDERR.

- **Then /^(STDOUT|STDERR) should be a number$/** - Expect STDOUT or STDERR to be a numeric value.
- **Then /^(STDOUT|STDERR) should not be a number$/** - Expect STDOUT or STDERR to not be a numeric value.
- **Then /^STDOUT should be a table containing rows:$/** - Expect STDOUT to be a table containing the given rows.
- **Then /^STDOUT should end with a table containing rows:$/** - Expect STDOUT to end with a table containing the given rows.
- **Then /^STDOUT should be JSON containing:$/** - Expect valid JSON output in STDOUT.
- **Then /^STDOUT should be a JSON array containing:$/** - Expect valid JSON array output in STDOUT.
- **Then /^STDOUT should be CSV containing:$/** - Expect STDOUT to be CSV containing certain values.
- **Then /^STDOUT should be YAML containing:$/** - Expect STDOUT to be YAML containing certain content.
- **Then /^(STDOUT|STDERR) should be empty$/** - Expect STDOUT or STDERR to be empty.
- **Then /^(STDOUT|STDERR) should not be empty$/** - Expect STDOUT or STDERR not to be empty.
- **Then /^(STDOUT|STDERR) should be a version string (<|<=|>|>=|==|=|!=|<>) ([+\w.{}-]+)$/** - Expect STDOUT or STDERR to be a version string comparing to the given version.
- **Then /^the (.+) (file|directory) should(strictly)? (exist|not exist|be:|contain:|not contain:)$/** - Expect a certain file or directory to (not) exist or (not) contain certain contents.
- **Then /^(STDOUT|STDERR) should(not)? match (((\/.+\/)|(#.+#))([a-z]+)?)$/** - Match STDOUT or STDERR against a regex.
- **Then /^an email should (be sent|not be sent)$/** - Expect an email to be sent (or not).
- **Then the HTTP status code should be :code** - Expect the HTTP status code for visiting `http://localhost:8080`.

□□□ #1
□ cocobook-sync □□□ 2026-10-28 11:38:13 UTC
□ cocobook-sync □□□ 2026-10-28 11:38:13 UTC