

WP_CLI::get_php_binary()



- [Usage](#)
 - [Notes](#)
 - [Related](#)
-

Get the path to the PHP binary used when executing WP-CLI.

Usage

```
WP_CLI::get_php_binary()
```

@return (string)

Notes

Environment values permit specific binaries to be indicated.

Note: moved to Utils, left for BC.

Internal API documentation is generated from the WP-CLI codebase on every release. To suggest improvements, please submit a pull request.

Related

- [WP_CLI\Utils\get_home_dir\(\)](#) - Get the home directory.
- [WP_CLI\Utils\trailingslashit\(\)](#) - Appends a trailing slash.
- [WP_CLI\Utils\is_stream\(\)](#) - Check if a path is a PHP stream URL.

- [WP_CLI\Utils\normalize_path\(\)](#) - Normalize a filesystem path.
 - [WP_CLI\Utils\get_temp_dir\(\)](#) - Get the system's temp directory. Warns user if it isn't writable.
 - [WP_CLI\Utils\make_temp_file\(\)](#) - Create a unique temporary file safely without following symlinks.
 - [WP_CLI\Utils\make_temp_dir\(\)](#) - Create a unique temporary directory safely without following symlinks.
 - [WP_CLI\Utils\get_php_binary\(\)](#) - Get the path to the PHP binary used when executing WP-CLI.
-

📄 #1

📄 cocobook-sync 📄 2026-10-28 11:40:46 UTC

📄 cocobook-sync 📄 2026-10-28 11:40:46 UTC