

WP_CLI::log()



- [Usage](#)
 - [Notes](#)
 - [Related](#)
-

Display informational message without prefix.

Usage

```
WP_CLI::log( $message, $newline = true )
```

\$message (string) Message to write to STDOUT.

\$newline (bool) Optional. Whether to append a newline to the end of the message. Default true.

@return (void)

Notes

Message is written to STDOUT, or discarded when `--quiet` flag is supplied.

```
# `wp cli update` lets user know of each step in the update process.  
WP_CLI::log( sprintf( 'Downloading from %s...', $download_url ) );
```

Internal API documentation is generated from the WP-CLI codebase on every release. To suggest improvements, please submit a pull request.

Related

- [**WP_CLI\Utils\format_items\(\)**](#) - Render a collection of items as an ASCII table, JSON, CSV, YAML, list of ids, or count.
 - [**WP_CLI\Utils\make_progress_bar\(\)**](#) - Create a progress bar to display percent completion of a given operation.
 - [**WP_CLI::colorize\(\)**](#) - Colorize a string for output.
 - [**WP_CLI::line\(\)**](#) - Display informational message without prefix, and ignore `--quiet`.
 - [**WP_CLI::success\(\)**](#) - Display success message prefixed with "Success: ".
 - [**WP_CLI::debug\(\)**](#) - Display debug message prefixed with "Debug: " when `--debug` is used.
 - [**WP_CLI::warning\(\)**](#) - Display warning message prefixed with "Warning: ".
 - [**WP_CLI::error\(\)**](#) - Display error message prefixed with "Error: " and exit script.
 - [**WP_CLI::halt\(\)**](#) - Halt script execution with a specific return code.
 - [**WP_CLI::error_multi_line\(\)**](#) - Display a multi-line error message in a red box. Doesn't exit script.
-

📄 #1

📄 cocobook-sync 📄 2025-06-25 18:05:32 UTC

📄 cocobook-sync 📄 2026-10-06 21:11:26 UTC