

WP_CLI::read_value()



- [Usage](#)
 - [Related](#)
-

Read a value, from various formats.

Usage

```
WP_CLI::read_value( $raw_value, $assoc_args = [] )
```

\$raw_value (string)

mixed> (array<string,>) \$assoc_args

@return (mixed)

Internal API documentation is generated from the WP-CLI codebase on every release. To suggest improvements, please submit a pull request.

Related

- [WP_CLI\Utils\launch_editor_for_input\(\)](#) - Launch system's \$EDITOR for the user to edit some text.
- [WP_CLI\Utils\get_flag_value\(\)](#) - Return the flag value or, if it's not set, the \$default value.
- [WP_CLI\Utils\report_batch_operation_results\(\)](#) - Report the results of the same operation against multiple resources.
- [WP_CLI\Utils\parse_str_to_argv\(\)](#) - Parse a string of command line arguments into an \$argv-esqe variable.
- [WP_CLI::confirm\(\)](#) - Ask for confirmation before running a destructive operation.
- [WP_CLI::has_config\(\)](#) - Confirm that a global configuration parameter does exist.
- [WP_CLI::get_config\(\)](#) - Get values of global configuration parameters.

📁 #1

📁 cocobook-sync 📁 2026-10-28 11:40:53 UTC

📁 cocobook-sync 📁 2026-10-28 11:40:53 UTC