

WP_CLI\Utils\get_flag_value()



- [Usage](#)
 - [Notes](#)
 - [Related](#)
-

Return the flag value or, if it's not set, the \$default value.

Usage

```
WP_CLI\Utils\get_flag_value( $assoc_args, $flag, $default = null )
```

mixed> (array<string|int,) \$assoc_args Arguments array.

\$flag (string|int) Flag to get the value.

\$default (mixed) Default value for the flag. Default: NULL.

@return (mixed)

Notes

Because flags can be negated (e.g. --no-quiet to negate --quiet), this function provides a safer alternative to using `isset( $assoc_args['quiet'] )` or similar.

Internal API documentation is generated from the WP-CLI codebase on every release. To suggest improvements, please submit a pull request.

Related

- [WP_CLI\Utils\launch_editor_for_input\(\)](#) - Launch system's \$EDITOR for the user to edit some text.

- [**WP_CLI\Utils\report_batch_operation_results\(\)**](#) - Report the results of the same operation against multiple resources.
 - [**WP_CLI\Utils\parse_str_to_argv\(\)**](#) - Parse a string of command line arguments into an \$argv-esqe variable.
 - [**WP_CLI::confirm\(\)**](#) - Ask for confirmation before running a destructive operation.
 - [**WP_CLI::read_value\(\)**](#) - Read a value, from various formats.
 - [**WP_CLI::has_config\(\)**](#) - Confirm that a global configuration parameter does exist.
 - [**WP_CLI::get_config\(\)**](#) - Get values of global configuration parameters.
-

☐☐ #1

☐ cocobook-sync ☐☐ 2026-10-28 11:41:04 UTC

☐ cocobook-sync ☐☐ 2026-10-28 11:41:04 UTC