

WP_CLI\Utils\launch_editor_for_input()



- [Usage](#)
 - [Related](#)
-

Launch system's \$EDITOR for the user to edit some text.

Usage

```
WP_CLI\Utils\launch_editor_for_input( $input, $title = WP-CLI, $ext = tmp )
```

\$input (string) Some form of text to edit (e.g. post content).

\$title (string) Title to display in the editor.

\$ext (string) Extension to use with the temp file.

@return (string|bool) text, if file is saved from editor; false, if no change to file.

Internal API documentation is generated from the WP-CLI codebase on every release. To suggest improvements, please submit a pull request.

Related

- [WP_CLI\Utils\get_flag_value\(\)](#) - Return the flag value or, if it's not set, the \$default value.
- [WP_CLI\Utils\report_batch_operation_results\(\)](#) - Report the results of the same operation against multiple resources.
- [WP_CLI\Utils\parse_str_to_argv\(\)](#) - Parse a string of command line arguments into an \$argv-esqe variable.
- [WP_CLI::confirm\(\)](#) - Ask for confirmation before running a destructive operation.

- [WP_CLI::read_value\(\)](#) - Read a value, from various formats.
 - [WP_CLI::has_config\(\)](#) - Confirm that a global configuration parameter does exist.
 - [WP_CLI::get_config\(\)](#) - Get values of global configuration parameters.
-

#1

📄 cocobook-sync 📄 2026-10-28 11:41:13 UTC

📄 cocobook-sync 📄 2026-10-28 11:41:13 UTC