@wordpress/dom-ready

- Installation
- API
  - default
- Browser support
- Contributing to this package

Execute callback after the DOM is loaded.

Installation

Install the module

```
npm install @wordpress/dom-ready --save
```

*This package assumes that your code will run in an **ES2015+** environment. If you're using an environment that has limited or no support for such language features and APIs, you should include the polyfill shipped in `@wordpress/babel-preset-default` in your code.*

API

default

Specify a function to execute when the DOM is fully loaded.

Usage

```
import domReady from '@wordpress/dom-ready';

domReady( function () {
```

```
    //do something after DOM loads.
} );
```

Parameters

- *callback* `VoidFunction`: A function to execute after the DOM is ready.

Browser support

See https://make.wordpress.org/core/handbook/best-practices/browser-support/

Contributing to this package

This is an individual package that’s part of the Gutenberg project. The project is organized as a monorepo. It’s made up of multiple self-contained software packages, each with a specific purpose.

The packages in this monorepo are published to npm and used by WordPress as well as other software projects.

To find out more about contributing to this package or Gutenberg as a whole, please read the project’s main contributor guide.

□□□ #2
□ □□□ □□□ 2026-10-31 18:18:37 UTC
□ □□□ □□□ 2026-10-31 18:18:38 UTC