

CheckboxControl



- [Design guidelines](#)
 - [Usage](#)
 - [When to use checkboxes](#)
 - [Parent and child checkboxes](#)
 - [Development guidelines](#)
 - [Usage](#)
 - [Props](#)
 - [label: string](#)
 - [help: string|Element](#)
 - [checked: boolean](#)
 - [onChange: function](#)
 - [indeterminate: boolean](#)
 - [Related components](#)
-

Checkboxes allow the user to select one or more items from a set.

Selected and unselected checkboxes

Design guidelines

Usage

When to use checkboxes

Use checkboxes when you want users to:

- Select one or multiple items from a list.
- Open a list containing sub-selections.

`select-from-list.png?ssl=1`

Do

Use checkboxes when users can select multiple items from a list. They let users select more than one item.

many-form-toggles.png?ssl=1

Don't

Don't use toggles when a list consists of multiple options. Use checkboxes — they take up less space.

checkbox-sublist.gif?ssl=1

Checkboxes can be used to open a list containing sub-selections.

Parent and child checkboxes

Checkboxes can have a parent-child relationship, with secondary options nested under primary options.

checkbox-parent.gif?ssl=1

When the parent checkbox is *checked*, all the child checkboxes are checked. When a parent checkbox is *unchecked*, all the child checkboxes are unchecked.

mixed-checkbox.png?ssl=1

If only a few child checkboxes are checked, the parent checkbox becomes a mixed checkbox.

Development guidelines

Usage

Render an author checkbox:

```
import { useState } from 'react';
import { CheckboxControl } from '@wordpress/components';

const MyCheckboxControl = () => {
  const [ isChecked, setChecked ] = useState( true );
  return (
    <CheckboxControl
      label="Is author"
      help="Is the user a author or not?"
      checked={ isChecked }
    />
  );
};
```

```
        onChange={ setChecked }  
      />  
    );  
  };
```

Props

The set of props accepted by the component will be specified below.
Props not included in this set will be applied to the input element.

label: `string`

A label for the input field, that appears at the side of the checkbox.
The prop will be rendered as content a label element.
If no prop is passed an empty label is rendered.

- Required: No

help: `string|Element`

If this property is added, a help text will be generated using help property as the content.

- Required: No

checked: `boolean`

If checked is true the checkbox will be checked. If checked is false the checkbox will be unchecked.
If no value is passed the checkbox will be unchecked.

- Required: No

onChange: `function`

A function that receives the checked state (boolean) as input.

- Required: Yes

indeterminate: `boolean`

If indeterminate is true the state of the checkbox will be indeterminate.

- Required: No

Related components

- To select one option from a set, and you want to show all the available options at once, use the `RadioControl` component.
 - To toggle a single setting on or off, use the `FormToggle` component.
-

☐☐☐ #2	
☐ ☐☐	☐☐ 2026-10-31 18:12:28 UTC
☐ ☐☐	☐☐ 2026-10-31 18:12:29 UTC