tag to content node connection

- title: "Tag to Content Node Connection" wordpressUri: "/recipes/tag-to-content-node-connection/" wor

title: "Tag to Content Node Connection" wordpressUri: "/recipes/tag-to-content-node-connection/" wordpressId: "2420" group: "Custom Post Types" summary: "The following code registers a connection from Tags to ContentNodes. A field name called contentNodes will be added to the Tag type to make it easy to

view all Posts that are tagged with that specific term. add_action('..."

The following code registers a connection from Tags to ContentNodes. A field name called contentNodes will be added to the Tag type to make it easy to view all Posts that are tagged with that specific term.

```
add_action( 'graphql_register_types', function() {
□register_graphql_connection([
□□'fromType' => 'Tag',
□□'toType' => 'ContentNode',
□□'fromFieldName' => 'contentNodes',
□□'resolve' => function( \WPGraphQL\Model\Term $source, $args, $context, $info ) {
□□□// Get all post types allowed in GraphQL
□□□$post_types = WPGraphQL::get_allowed_post_types();

□□□// Instantiate a new PostObjectConnectionResolver class
□□□$resolver = new \WPGraphQL\Data\Connection\PostObjectConnectionResolver( $source, $args, $context, $info, $post_types );

□□□// Set the argument that will be passed to WP_Query. We want only Posts (of any post type) that are tagged with this Tag's ID
□□□$resolver->set_query_arg( 'tag_id', $source->term_id );

□□□// Return the connection
□□□return $resolver->get_connection();
□□}
□]);
} );
```

□□□ #2
□ □□□ □□□ 2026-08-29 15:36:26 UTC
□ □□□ □□□ 2026-08-29 15:36:26 UTC