

Testing



- [Testing with wp-env](#)
 - [Prerequisites](#)
 - [Installation](#)
 - [Custom Test Environments](#)
 - [Running the Tests](#)
 - [Mocking Outbound HTTP in Tests](#)
 - [Smoke Tests](#)
 - [Testing the Production Zip](#)
 - [Testing Locally with Codeception](#)
 - [Pre-requisites](#)
 - [Install WordPress Test Environment](#)
 - [Configure Test Suites](#)
 - [Install Composer Dependencies](#)
 - [Run the tests](#)
-

This document will be most useful for developers that want to contribute to WPGraphQL and want to run tests locally.

In order to run tests, you must [clone the monorepo from GitHub](#). The WPGraphQL plugin is located at `plugins/wp-graphql/` in the repository. Downloading from Composer or Packagist will not include the dev dependencies needed to run tests.

“ **Note:** WPGraphQL is now a monorepo. For detailed testing instructions, see the [Testing Guide](#) in the repository root.

Testing with wp-env

The easiest way to run tests is to use the included `wp-env` setup. This uses Docker to create a local WordPress environment with WPGraphQL installed as a plugin.

Prerequisites

- Node.js 22+ and npm >= 10 (NVM recommended)
- Docker
- Git

Installation

1. Clone the repository:

```
git clone git@github.com:wp-graphql/wp-graphql.git
cd wp-graphql
```

2. Install the NPM dependencies (from the repository root):

```
## If you're using nvm, make sure to use the correct Node.js version:
nvm install && nvm use

## Then install the NPM dependencies:
npm install
```

3. Start the `wp-env` environment to download and set up the Docker containers for WordPress:

```
npm run wp-env start
```

When finished, the WordPress development site will be available at `http://localhost:8888` and the WP Admin Dashboard will be available at `http://localhost:8888/wp-admin/`. You can log in to the admin using the username `admin` and password `password`.

Composer dependencies are automatically installed when the environment starts.

4. (Optional) Manually install Composer dependencies:

```
## To install Composer dependencies inside the Docker container:
npm run wp-env -- run tests-cli --env-cwd=wp-content/plugins/wp-graphql/ -- composer
install
```

Custom Test Environments

If you need to customize the `wp-env` environment (for example to add additional plugins, or change PHP versions), you can do so by creating a `.wp-env.override.json` file in the root of the plugin.

For example:

```
{
  "core": "WordPress/WordPress#6.5", # To use a specific version of WordPress
  "phpVersion": "8.1", # To use a specific PHP version
}
```

For more information on using and overriding `wp-env` settings, see the [@wordpress/env](https://developer.wordpress.org/packages-and-plugins/development/testing/containers/wordpress-environment/) [package documentation](https://developer.wordpress.org/packages-and-plugins/development/testing/containers/wordpress-environment/).

Running the Tests

To access Codeception and run tests inside the `wp-env` Docker container, use the following commands from the repository root:

```
## WPUnit tests
npm run -w @wpgraphql/wp-graphql test:codecept:wpunit

## Acceptance tests
npm run -w @wpgraphql/wp-graphql test:codecept:acceptance

## Functional tests
npm run -w @wpgraphql/wp-graphql test:codecept:functional
```

For example:

```
## Run all WPUnit tests
npm run -w @wpgraphql/wp-graphql test:codecept:wpunit

## Just a single test file
npm run -w @wpgraphql/wp-graphql test:codecept:wpunit -- tests/wpunit/AccessFunctionsTest.php

## Or a single test within a file
npm run -w @wpgraphql/wp-graphql test:codecept:wpunit --
tests/wpunit/AccessFunctionsTest.php:testCustomScalarCanBeUsedInSchema
```

```
## With verbose debugging
npm run -w @wpgraphql/wp-graphql test:codecept:wpunit -- --debug

## With a specific theme
TEST_THEME=twentytwentyfive npm run -w @wpgraphql/wp-graphql test:codecept:wpunit
```

Mocking Outbound HTTP in Tests

Tests that exercise code which fetches remote URLs (for example, media sideloading) must never make real network requests. The convention is:

- **Use RFC 5737 TEST-NET addresses** for any URL the test fabricates: `192.0.2.0/24` (TEST-NET-1), `198.51.100.0/24` (TEST-NET-2), or `203.0.113.0/24` (TEST-NET-3). These ranges are reserved for documentation and are guaranteed never to route to a real host, so even if a mock fails to intercept, no traffic leaves the machine.
- **Intercept the request** with the `pre_http_request` filter and return a fabricated response.
- **Allow the host through URL validation.** Since WordPress 7.1, `wp_http_validate_url()` rejects reserved and documentation IP ranges (including the TEST-NET blocks), so any URL that passes through `wp_safe_remote_get()` / `download_url()` is rejected before your `pre_http_request` mock ever runs. Explicitly allow the specific test host via the `http_request_host_is_external` filter:

```
$allow_test_net = static function ( $external, $host ) {
    return '203.0.113.42' === $host ? true : $external;
};

add_filter( 'http_request_host_is_external', $allow_test_net, 10, 2 );

// ... run the code under test ...

remove_filter( 'http_request_host_is_external', $allow_test_net, 10 );
```

Scope the filter to the exact host the test uses (don't return `true` unconditionally), and remove it when the test is done. See

`tests/wpunit/MediaItemMutationsTest.php::testCreateMediaItemSideloadFailureIsSurfaced` for a complete example.

Smoke Tests

Smoke tests are lightweight tests that verify the plugin works correctly without running the full test suite. They're useful for quickly validating builds.

```
## Run smoke tests against a running WordPress environment
./bin/smoke-test.sh

## With a custom endpoint
./bin/smoke-test.sh --endpoint http://wpgraphql.local/graphql

## With verbose output
./bin/smoke-test.sh --verbose
```

Smoke tests verify:

- GraphQL endpoint responds
- Introspection works
- Basic queries (posts, pages, users, etc.) work
- Site settings are accessible

Testing the Production Zip

To test the actual production zip artifact (mimicking CI), you need to install the plugin via WP-CLI rather than mounting it via wp-env. See the [Testing Guide](#) for detailed instructions.

Testing Locally with Codeception

On some machines, running tests directly with Codeception may be faster than using Docker. If for performance or any other reasons you want to run tests directly on your machine, you can follow the instructions below.

Pre-requisites

- Command line access
- PHP 7.4+ installed and running on your machine
- MySQL installed and running on your machine
- Composer

Install WordPress Test Environment

WPGraphQL includes a script to install a local test environment, using the environment variables you provide in a `.env` file.

1. Navigate to the WPGraphQL plugin directory:

```
cd plugins/wp-graphql
```

2. Copy the `.env.dist` file to a new file named `.env` and update variables to match your local database setup.
3. Run the test environment setup script:

```
composer install-test-env
```

The script will download and install a local WordPress installation in the provided directory, set up the database, and install WPGraphQL.

Configure Test Suites

Within the `plugins/wp-graphql/tests/` directory are the Codeception `.yaml` configuration files.

To run tests locally, copy the `.yaml` file for the test suite you want to run and rename it without the `.dist`.

For example:

- copy: `wpunit.suite.dist.yaml` to `wpunit.suite.yaml`

Then update the details of the `.yaml` file to point to your local database by changing the fields:

- dbName
- dbHost
- dbUser
- dbPassword

The other fields should be able to remain the same, but update as necessary.

Install Composer Dependencies

Run the following from the WPGraphQL plugin directory (`plugins/wp-graphql/`):

```
composer install
```

This installs the dev dependencies needed to run the tests.

Run the tests

To run the tests from the plugin directory, use the following commands (you can use `control + c` to exit):

```
vendor/bin/codecept run wpunit
```

This will run *all* of the tests of the `wpunit` suite.

To run an individual test file, you can specify the file like so:

```
vendor/bin/codecept run tests/wpunit/AccessFunctionsTest.php
```

Or you can specify one specific test like so:

```
vendor/bin/codecept run tests/wpunit/AccessFunctionsTest.php:testCustomScalarCanBeUsedInSchema
```

The tests should start running and you should see something similar to the following:

Screenshot of Codeception tests running in the terminal.

```
## #1
# ## 2026-08-29 15:36:26 UTC
# ## 2026-08-29 15:36:26 UTC
```