Statuses

- Schema
- Retrieve a Status
- Retrieve a Status

Schema

The schema defines all the fields that exist within a status record. Any response from these endpoints can be expected to contain the fields below unless the `_filter` query parameter is used or the schema field only appears in a specific context.

`name`	The title for the status. JSON data type: string Read only Context: `embed`, `view`, `edit`
`private`	Whether posts with this status should be private. JSON data type: boolean Read only Context: `edit`
`protected`	Whether posts with this status should be protected. JSON data type: boolean Read only Context: `edit`
`public`	Whether posts of this status should be shown in the front end of the site. JSON data type: boolean Read only Context: `view`, `edit`
`queryable`	Whether posts with this status should be publicly-queryable. JSON data type: boolean Read only Context: `view`, `edit`

`show_in_list`	Whether to include posts in the edit listing for their post type. JSON data type: boolean Read only Context: `edit`
`slug`	An alphanumeric identifier for the status. JSON data type: string Read only Context: `embed`, `view`, `edit`
`date_floating`	Whether posts of this status may have floating published dates. JSON data type: boolean Read only Context: `view`, `edit`

```
</div>
```

Retrieve a Status

```
□<h3>Definition & Example Request</h3>

□<code>GET /wp/v2/statuses</code>

□<p>Query this endpoint to retrieve a specific status record.</p>

□<code>$ curl https://example.com/wp-json/wp/v2/statuses</code>
</div>
<div class="secondary">
□□<h3>Arguments</h3>
<table class="arguments">
□□□□<tr>
□□□<td>
□□□□□□□□□□<code>context</code><br />
□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□<p>Scope under which the request is made; determines fields present in response.</p>
□□□□□□□□□□□□□□□□□□□□□□□□□□<p class="default">
□□□□□□□Default: <code>view</code>
□□□□□□</p>
□□□□□□□□□□□□□□□□□<p>One of: <code>view</code>, <code>embed</code>, <code>edit</code></p>
```

```
□□□□□□□□□</td>
□□</tr>
□□</table>

</div>
```

Retrieve a Status

```
□<h3>Definition & Example Request</h3>

□<code>GET /wp/v2/statuses/&lt;status&gt;</code>

□<p>Query this endpoint to retrieve a specific status record.</p>

□<code>$ curl https://example.com/wp-json/wp/v2/statuses/&lt;status&gt;</code>
</div>
<div class="secondary">
□□<h3>Arguments</h3>
<table class="arguments">
□□□□<tr>
□□□<td>
□□□□□□□□□□<code>status</code><br />
□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□<p>An alphanumeric identifier for the status.</p>
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□</td>
□□</tr>
□□□□<tr>
□□□<td>
□□□□□□□□□□<code>context</code><br />
□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□<p>Scope under which the request is made; determines fields present in response.</p>
□□□□□□□□□□□□□□□□□□□□□□□□□□<p class="default">
□□□□□□□Default: <code>view</code>
□□□□□□</p>
□□□□□□□□□□□□□□□□□<p>One of: <code>view</code>, <code>embed</code>, <code>edit</code></p>
```

□□□□□□□□□</td>

□□</tr>

□□</table>

□□□ #2

□ □□□ □□□ 2026-08-29 15:39:08 UTC

□ □□□ □□□ 2026-08-29 15:39:08 UTC