Posts

- Schema
- List Posts
- Create a Post
  - Arguments
- Retrieve a Post
- Update a Post
  - Arguments
- Delete a Post
  - Arguments

Schema

The schema defines all the fields that exist within a post record. Any response from these endpoints can be expected to contain the fields below unless the `_filter` query parameter is used or the schema field only appears in a specific context.

`date`	The date the post was published, in the site's timezone. JSON data type: string or null, Format: datetime (details) Context: `view`, `edit`, `embed`
`date_gmt`	The date the post was published, as GMT. JSON data type: string or null, Format: datetime (details) Context: `view`, `edit`
`guid`	The globally unique identifier for the post. JSON data type: object Read only Context: `view`, `edit`
`id`	Unique identifier for the post. JSON data type: integer Read only Context: `view`, `edit`, `embed`

`link`	URL to the post. JSON data type: string, Format: uri Read only Context: `view`, `edit`, `embed`
`modified`	The date the post was last modified, in the site's timezone. JSON data type: string, Format: datetime (details) Read only Context: `view`, `edit`
`modified_gmt`	The date the post was last modified, as GMT. JSON data type: string, Format: datetime (details) Read only Context: `view`, `edit`
`slug`	An alphanumeric identifier for the post unique to its type. JSON data type: string Context: `view`, `edit`, `embed`
`status`	A named status for the post. JSON data type: string Context: `view`, `edit` One of: `publish`, `future`, `draft`, `pending`, `private`
`type`	Type of post. JSON data type: string Read only Context: `view`, `edit`, `embed`
`password`	A password to protect access to the content and excerpt. JSON data type: string Context: `edit`
`permalink_template`	Permalink template for the post. JSON data type: string Read only Context: `edit`
`generated_slug`	Slug automatically generated from the post title. JSON data type: string Read only Context: `edit`
`title`	The title for the post. JSON data type: object Context: `view`, `edit`, `embed`
`content`	The content for the post. JSON data type: object Context: `view`, `edit`
`author`	The ID for the author of the post. JSON data type: integer Context: `view`, `edit`, `embed`
`excerpt`	The excerpt for the post. JSON data type: object Context: `view`, `edit`, `embed`

`featured_media`	The ID of the featured media for the post. JSON data type: integer Context: `view`, `edit`, `embed`
`comment_status`	Whether or not comments are open on the post. JSON data type: string Context: `view`, `edit` One of: `open`, `closed`
`ping_status`	Whether or not the post can be pinged. JSON data type: string Context: `view`, `edit` One of: `open`, `closed`
`format`	The format for the post. JSON data type: string Context: `view`, `edit` One of: `standard`, `aside`, `chat`, `gallery`, `link`, `image`, `quote`, `status`, `video`, `audio`
`meta`	Meta fields. JSON data type: object Context: `view`, `edit`
`sticky`	Whether or not the post should be treated as sticky. JSON data type: boolean Context: `view`, `edit`
`template`	The theme file to use to display the post. JSON data type: string Context: `view`, `edit`
`categories`	The terms assigned to the post in the category taxonomy. JSON data type: array Context: `view`, `edit`
`tags`	The terms assigned to the post in the post_tag taxonomy. JSON data type: array Context: `view`, `edit`

```
</div>
```

List Posts

Query this endpoint to retrieve a collection of posts. The response you receive can be controlled and filtered using the URL query parameters below.

```
<h3>Definition</h3>

<code>GET /wp/v2/posts</code>
```

```
□<h3>Example Request</h3>

□<code>$ curl https://example.com/wp-json/wp/v2/posts</code>
</div>
<div class="secondary">
□□<h3>Arguments</h3>
<table class="arguments">
□□□□<tr>
□□□<td>
□□□□□□□□□□□<code>context</code><br />
□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□□<p>Scope under which the request is made; determines fields present in response.</p>
□□□□□□□□□□□□□□□□□□□□□□□□□□□<p class="default">
□□□□□□□Default: <code>view</code>
□□□□□□</p>
□□□□□□□□□□□□□□□□□<p>One of: <code>view</code>, <code>embed</code>, <code>edit</code></p>
□□□□□□□□□</td>
□□</tr>
□□□□<tr>
□□□<td>
□□□□□□□□□□□<code>page</code><br />
□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□□<p>Current page of the collection.</p>
□□□□□□□□□□□□□□□□□□□□□□□□□□□<p class="default">
□□□□□□□Default: <code>1</code>
□□□□□□</p>
□□□□□□□□□□□□□□□□</td>
□□</tr>
□□□□<tr>
□□□<td>
□□□□□□□□□□□<code>per_page</code><br />
□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□□<p>Maximum number of items to be returned in result set.</p>
□□□□□□□□□□□□□□□□□□□□□□□□□□□<p class="default">
□□□□□□□Default: <code>10</code>
□□□□□□</p>
```

□□□□□□□□□□□□□□□□</td>
□□</tr>
□□□□<tr>
□□□<td>
□□□□□□□□□□□<code>search</code>
□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□□ Limit results to those matching a string.
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□</td>
□□</tr>
□□□□<tr>
□□□<td>
□□□□□□□□□□□<code>after</code>
□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□□ Limit response to posts published after a given ISO8601 compliant date.
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□</td>
□□</tr>
□□□□<tr>
□□□<td>
□□□□□□□□□□□<code>modified_after</code>
□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□□ Limit response to posts modified after a given ISO8601 compliant date.
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□</td>
□□</tr>
□□□□<tr>
□□□<td>
□□□□□□□□□□□<code>author</code>
□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□□ Limit result set to posts assigned to specific authors.
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□</td>
□□</tr>
□□□□<tr>
□□□<td>
□□□□□□□□□□□<code>author_exclude</code>
□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□□ Ensure result set excludes posts assigned to specific authors.

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□</td>
□□</tr>
□□□□<tr>
□□□<td>
□□□□□□□□□□□<code>before</code>
□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□□ Limit response to posts published before a given ISO8601 compliant date.
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□</td>
□□</tr>
□□□□<tr>
□□□<td>
□□□□□□□□□□□<code>modified_before</code>
□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□□ Limit response to posts modified before a given ISO8601 compliant date.
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□</td>
□□</tr>
□□□□<tr>
□□□<td>
□□□□□□□□□□□<code>exclude</code>
□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□□ Ensure result set excludes specific IDs.
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□</td>
□□</tr>
□□□□<tr>
□□□<td>
□□□□□□□□□□□<code>include</code>
□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□□ Limit result set to specific IDs.
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□</td>
□□</tr>
□□□□<tr>
□□□<td>
□□□□□□□□□□□<code>offset</code>
□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□□ Offset the result set by a specific number of items.

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□</td>
□□</tr>
□□□□<tr>
□□□<td>
□□□□□□□□□□□□<code>order</code>
□□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□□□ Order sort attribute ascending or descending.
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□□□□□Default: <code>desc</code>
□□□□□□
□□□□□□□□□□□□□□□□□□ One of: <code>asc</code>, <code>desc</code>
□□□□□□□□□□</td>
□□</tr>
□□□□<tr>
□□□<td>
□□□□□□□□□□□□<code>orderby</code>
□□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□□□ Sort collection by post attribute.
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□□□□□Default: <code>date</code>
□□□□□□
□□□□□□□□□□□□□□□□□□ One of: <code>author</code>, <code>date</code>, <code>id</code>, <code>includ
<code>modified</code>, <code>parent</code>, <code>relevance</code>, <code>slug</code>,
<code>include_slugs</code>, <code>title</code>
□□□□□□□□□□</td>
□□</tr>
□□□□<tr>
□□□<td>
□□□□□□□□□□□□<code>search_columns</code>
□□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□□□ Array of column names to be searched.
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□</td>
□□</tr>
□□□□<tr>
□□□<td>
□□□□□□□□□□□□<code>slug</code>
□□□□□□□□□□</td>

□□□<td>
□□□□□□□□□□□ Limit result set to posts with one or more specific slugs.
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□</td>
□□</tr>
□□□□<tr>
□□□<td>
□□□□□□□□□□□<code>status</code>
□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□□ Limit result set to posts assigned one or more statuses.
□□□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□□□□□Default: <code>publish</code>
□□□□□
□□□□□□□□□□□□□□□□</td>
□□</tr>
□□□□<tr>
□□□<td>
□□□□□□□□□□□<code>tax_relation</code>
□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□□ Limit result set based on relationship between multiple taxonomies.
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ One of: <code>AND</code>, <code>OR</code>
□□□□□□□□□</td>
□□</tr>
□□□□<tr>
□□□<td>
□□□□□□□□□□□<code>categories</code>
□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□□ Limit result set to items with specific terms assigned in the categories taxonomy.
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□</td>
□□</tr>
□□□□<tr>
□□□<td>
□□□□□□□□□□□<code>categories_exclude</code>
□□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□□ Limit result set to items except those with specific terms assigned in the categor
taxonomy.
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□</td>

```
□□</tr>
□□□□<tr>
□□□<td>
□□□□□□□□□□<code>tags</code><br />
□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□<p>Limit result set to items with specific terms assigned in the tags taxonomy.</p>
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□</td>
□□</tr>
□□□□<tr>
□□□<td>
□□□□□□□□□□<code>tags_exclude</code><br />
□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□<p>Limit result set to items except those with specific terms assigned in the tags
taxonomy.</p>
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□</td>
□□</tr>
□□□□<tr>
□□□<td>
□□□□□□□□□□<code>sticky</code><br />
□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□<p>Limit result set to items that are sticky.</p>
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□</td>
□□</tr>
□□</table>

</div>
```

Create a Post

Arguments

`date`	The date the post was published, in the site's timezone.
`date_gmt`	The date the post was published, as GMT.

`slug`	An alphanumeric identifier for the post unique to its type.
`status`	A named status for the post. One of: `publish`, `future`, `draft`, `pending`, `private`
`password`	A password to protect access to the content and excerpt.
`title`	The title for the post.
`content`	The content for the post.
`author`	The ID for the author of the post.
`excerpt`	The excerpt for the post.
`featured_media`	The ID of the featured media for the post.
`comment_status`	Whether or not comments are open on the post. One of: `open`, `closed`
`ping_status`	Whether or not the post can be pinged. One of: `open`, `closed`
`format`	The format for the post. One of: `standard`, `aside`, `chat`, `gallery`, `link`, `image`, `quote`, `status`, `video`, `audio`
`meta`	Meta fields.
`sticky`	Whether or not the post should be treated as sticky.
`template`	The theme file to use to display the post.
`categories`	The terms assigned to the post in the category taxonomy.
`tags`	The terms assigned to the post in the post_tag taxonomy.

```
</div>
<div class="secondary">
□<h3>Definition</h3>

□<code>POST /wp/v2/posts</code>
</div>
```

Retrieve a Post

```
□<h3>Definition & Example Request</h3>

□<code>GET /wp/v2/posts/&lt;id&gt;</code>
```

```
□<p>Query this endpoint to retrieve a specific post record.</p>

□<code>$ curl https://example.com/wp-json/wp/v2/posts/<id></code>
</div>
<div class="secondary">
□□<h3>Arguments</h3>
<table class="arguments">
□□□□<tr>
□□□<td>
□□□□□□□□□□□<code>id</code><br />
□□□□□□□□□</td>
□□□<td>
□□□□□□□□□□□<p>Unique identifier for the post.</p>
□□□□□□□□□□□
```

Update a Post

Arguments

`id`	Unique identifier for the post.
`date`	The date the post was published, in the site's timezone.
`date_gmt`	The date the post was published, as GMT.
`slug`	An alphanumeric identifier for the post unique to its type.
`status`	A named status for the post. One of: `publish`, `future`, `draft`, `pending`, `private`
`password`	A password to protect access to the content and excerpt.
`title`	The title for the post.
`content`	The content for the post.
`author`	The ID for the author of the post.
`excerpt`	The excerpt for the post.
`featured_media`	The ID of the featured media for the post.
`comment_status`	Whether or not comments are open on the post. One of: `open`, `closed`
`ping_status`	Whether or not the post can be pinged. One of: `open`, `closed`
`format`	The format for the post. One of: `standard`, `aside`, `chat`, `gallery`, `link`, `image`, `quote`, `status`, `video`, `audio`
`meta`	Meta fields.
`sticky`	Whether or not the post should be treated as sticky.
`template`	The theme file to use to display the post.
`categories`	The terms assigned to the post in the category taxonomy.
`tags`	The terms assigned to the post in the post_tag taxonomy.

```
</div>
<div class="secondary">
<h3>Definition</h3>
```

```
□<code>POST /wp/v2/posts/&lt;id&gt;</code>

□<h3>Example Request</h3>

□<code>$ curl -X POST https://example.com/wp-json/wp/v2/posts/&lt;id&gt; -d '{"title":"My New Title"}'
```

Delete a Post

Arguments

`id`	Unique identifier for the post.
`force`	Whether to bypass Trash and force deletion.

```
</div>
<div class="secondary">
□<h3>Definition</h3>

□<code>DELETE /wp/v2/posts/&lt;id&gt;</code>

□<h3>Example Request</h3>

□<code>$ curl -X DELETE https://example.com/wp-json/wp/v2/posts/&lt;id&gt;</code>
</div>
```

□□□ #2
□ □□□ □□□ 2025-06-04 15:42:29 UTC
□ □□□ □□□ 2025-06-04 15:42:29 UTC