Posts

- Schema
- List Posts
  - Definition
  - Example Request
  - Arguments
- Create a Post
  - Arguments
  - Definition
- Retrieve a Post
  - Definition & Example Request
  - Arguments
- Update a Post
  - Arguments
  - Definition
  - Example Request
- Delete a Post
  - Arguments
  - Definition
  - Example Request

Schema

The schema defines all the fields that exist within a post record. Any response from these endpoints can be expected to contain the fields below unless the `_filter` query parameter is used or the schema field only appears in a specific context.

`date`	The date the post was published, in the site’s timezone. JSON data type: string or null, Format: datetime (details) Context: `view`, `edit`, `embed`
`date_gmt`	The date the post was published, as GMT. JSON data type: string or null, Format: datetime (details) Context: `view`, `edit`
`guid`	The globally unique identifier for the post. JSON data type: object Read only Context: `view`, `edit`
`id`	Unique identifier for the post. JSON data type: integer Read only Context: `view`, `edit`, `embed`
`link`	URL to the post. JSON data type: string, Format: uri Read only Context: `view`, `edit`, `embed`
`modified`	The date the post was last modified, in the site’s timezone. JSON data type: string, Format: datetime (details) Read only Context: `view`, `edit`
`modified_gmt`	The date the post was last modified, as GMT. JSON data type: string, Format: datetime (details) Read only Context: `view`, `edit`
`slug`	An alphanumeric identifier for the post unique to its type. JSON data type: string Context: `view`, `edit`, `embed`
`status`	A named status for the post. JSON data type: string Context: `view`, `edit` One of: `publish`, `future`, `draft`, `pending`, `private`
`type`	Type of post. JSON data type: string Read only Context: `view`, `edit`, `embed`
`password`	A password to protect access to the content and excerpt. JSON data type: string Context: `edit`

`permalink_template`	Permalink template for the post. JSON data type: string Read only Context: `edit`
`generated_slug`	Slug automatically generated from the post title. JSON data type: string Read only Context: `edit`
`title`	The title for the post. JSON data type: object Context: `view`, `edit`, `embed`
`content`	The content for the post. JSON data type: object Context: `view`, `edit`
`author`	The ID for the author of the post. JSON data type: integer Context: `view`, `edit`, `embed`
`excerpt`	The excerpt for the post. JSON data type: object Context: `view`, `edit`, `embed`
`featured_media`	The ID of the featured media for the post. JSON data type: integer Context: `view`, `edit`, `embed`
`comment_status`	Whether or not comments are open on the post. JSON data type: string Context: `view`, `edit` One of: `open`, `closed`
`ping_status`	Whether or not the post can be pinged. JSON data type: string Context: `view`, `edit` One of: `open`, `closed`
`format`	The format for the post. JSON data type: string Context: `view`, `edit` One of: `standard`, `aside`, `chat`, `gallery`, `link`, `image`, `quote`, `status`, `video`, `audio`
`meta`	Meta fields. JSON data type: object Context: `view`, `edit`
`sticky`	Whether or not the post should be treated as sticky. JSON data type: boolean Context: `view`, `edit`
`template`	The theme file to use to display the post. JSON data type: string Context: `view`, `edit`

`categories`	The terms assigned to the post in the category taxonomy. JSON data type: array Context: `view`, `edit`
`tags`	The terms assigned to the post in the post_tag taxonomy. JSON data type: array Context: `view`, `edit`

List Posts

Query this endpoint to retrieve a collection of posts. The response you receive can be controlled and filtered using the URL query parameters below.

Definition

`GET /wp/v2/posts`

Example Request

```
$ curl https://example.com/wp-json/wp/v2/posts
```

Arguments

`context`	Scope under which the request is made; determines fields present in response. Default: `view` One of: `view`, `embed`, `edit`
`page`	Current page of the collection. Default: `1`
`per_page`	Maximum number of items to be returned in result set. Default: `10`
`search`	Limit results to those matching a string.
`after`	Limit response to posts published after a given ISO8601 compliant date.
`modified_after`	Limit response to posts modified after a given ISO8601 compliant date.
`author`	Limit result set to posts assigned to specific authors.

`author_exclude`	Ensure result set excludes posts assigned to specific authors.
`before`	Limit response to posts published before a given ISO8601 compliant date.
`modified_before`	Limit response to posts modified before a given ISO8601 compliant date.
`exclude`	Ensure result set excludes specific IDs.
`include`	Limit result set to specific IDs.
`offset`	Offset the result set by a specific number of items.
`order`	Order sort attribute ascending or descending. Default: `desc` One of: `asc`, `desc`
`orderby`	Sort collection by post attribute. Default: `date` One of: `author`, `date`, `id`, `include`, `modified`, `parent`, `relevance`, `slug`, `include_slugs`, `title`
`search_columns`	Array of column names to be searched.
`slug`	Limit result set to posts with one or more specific slugs.
`status`	Limit result set to posts assigned one or more statuses. Default: `publish`
`tax_relation`	Limit result set based on relationship between multiple taxonomies. One of: `AND`, `OR`
`categories`	Limit result set to items with specific terms assigned in the categories taxonomy.
`categories_exclude`	Limit result set to items except those with specific terms assigned in the categories taxonomy.
`tags`	Limit result set to items with specific terms assigned in the tags taxonomy.
`tags_exclude`	Limit result set to items except those with specific terms assigned in the tags taxonomy.
`sticky`	Limit result set to items that are sticky.

Create a Post

Arguments

`date`	The date the post was published, in the site's timezone.
`date_gmt`	The date the post was published, as GMT.
`slug`	An alphanumeric identifier for the post unique to its type.
`status`	A named status for the post. One of: `publish`, `future`, `draft`, `pending`, `private`
`password`	A password to protect access to the content and excerpt.
`title`	The title for the post.
`content`	The content for the post.
`author`	The ID for the author of the post.
`excerpt`	The excerpt for the post.
`featured_media`	The ID of the featured media for the post.
`comment_status`	Whether or not comments are open on the post. One of: `open`, `closed`
`ping_status`	Whether or not the post can be pinged. One of: `open`, `closed`
`format`	The format for the post. One of: `standard`, `aside`, `chat`, `gallery`, `link`, `image`, `quote`, `status`, `video`, `audio`
`meta`	Meta fields.
`sticky`	Whether or not the post should be treated as sticky.
`template`	The theme file to use to display the post.
`categories`	The terms assigned to the post in the category taxonomy.
`tags`	The terms assigned to the post in the post_tag taxonomy.

Definition

`POST /wp/v2/posts`

Retrieve a Post

Definition & Example Request

`GET /wp/v2/posts/<id>`

Query this endpoint to retrieve a specific post record.

```
$ curl https://example.com/wp-json/wp/v2/posts/<id>
```

Arguments

`id`	Unique identifier for the post.
`context`	Scope under which the request is made; determines fields present in response. Default: `view` One of: `view`, `embed`, `edit`
`password`	The password for the post if it is password protected.

Update a Post

Arguments

`id`	Unique identifier for the post.
`date`	The date the post was published, in the site's timezone.
`date_gmt`	The date the post was published, as GMT.
`slug`	An alphanumeric identifier for the post unique to its type.
`status`	A named status for the post. One of: `publish`, `future`, `draft`, `pending`, `private`
`password`	A password to protect access to the content and excerpt.
`title`	The title for the post.
`content`	The content for the post.
`author`	The ID for the author of the post.
`excerpt`	The excerpt for the post.
`featured_media`	The ID of the featured media for the post.
`comment_status`	Whether or not comments are open on the post. One of: `open`, `closed`
`ping_status`	Whether or not the post can be pinged. One of: `open`, `closed`

`format`	The format for the post. One of: `standard`, `aside`, `chat`, `gallery`, `link`, `image`, `quote`, `status`, `video`, `audio`
`meta`	Meta fields.
`sticky`	Whether or not the post should be treated as sticky.
`template`	The theme file to use to display the post.
`categories`	The terms assigned to the post in the category taxonomy.
`tags`	The terms assigned to the post in the post_tag taxonomy.

Definition

`POST /wp/v2/posts/<id>`

Example Request

```
$ curl -X POST https://example.com/wp-json/wp/v2/posts/<id> -d '{"title":"My New Title"}' \
```

Delete a Post

Arguments

`id`	Unique identifier for the post.
`force`	Whether to bypass Trash and force deletion.

Definition

`DELETE /wp/v2/posts/<id>`

Example Request

```
$ curl -X DELETE https://example.com/wp-json/wp/v2/posts/<id>
```

□□□ #2
□ □□□ □□□ 2026-10-31 13:39:23 UTC
□ □□□ □□□ 2026-10-31 13:39:24 UTC