Statuses

- Schema
- Retrieve a Status
  - Definition & Example Request
  - Arguments
- Retrieve a Status
  - Definition & Example Request
  - Arguments

Schema

The schema defines all the fields that exist within a status record. Any response from these endpoints can be expected to contain the fields below unless the `_filter` query parameter is used or the schema field only appears in a specific context.

`name`	The title for the status. JSON data type: string Read only Context: `embed`, `view`, `edit`
`private`	Whether posts with this status should be private. JSON data type: boolean Read only Context: `edit`
`protected`	Whether posts with this status should be protected. JSON data type: boolean Read only Context: `edit`
`public`	Whether posts of this status should be shown in the front end of the site. JSON data type: boolean Read only Context: `view`, `edit`

`queryable`	Whether posts with this status should be publicly-queryable. JSON data type: boolean Read only Context: `view`, `edit`
`show_in_list`	Whether to include posts in the edit listing for their post type. JSON data type: boolean Read only Context: `edit`
`slug`	An alphanumeric identifier for the status. JSON data type: string Read only Context: `embed`, `view`, `edit`
`date_floating`	Whether posts of this status may have floating published dates. JSON data type: boolean Read only Context: `view`, `edit`

Retrieve a Status

Definition & Example Request

`GET /wp/v2/statuses`

Query this endpoint to retrieve a specific status record.

```
$ curl https://example.com/wp-json/wp/v2/statuses
```

Arguments

`context`	Scope under which the request is made; determines fields present in response. Default: `view` One of: `view`, `embed`, `edit`

Retrieve a Status

Definition & Example Request

`GET /wp/v2/statuses/<status>`

Query this endpoint to retrieve a specific status record.

```
$ curl https://example.com/wp-json/wp/v2/statuses/<status>
```

Arguments

`status`	An alphanumeric identifier for the status.
`context`	Scope under which the request is made; determines fields present in response. Default: `view` One of: `view`, `embed`, `edit`

□□□ #2
□ □□□ □□□ 2026-10-31 13:39:36 UTC
□ □□□ □□□ 2026-10-31 13:39:37 UTC