Coding Guidelines And Principles

□□

- PHP □□□□
- JavaScript □□□□
- □□□□
- □□□□
  - □□□□□□□ KISS□
  - □□□□□□□ DRY□
  - SOLID
  - □□
    - □□□□□□ (TDD)
  - □□□□□□
- □□
  - □□ /□□ “□□ ”□□
  - □□ .js □ .css □□
  - PHPDocs □□□

PHP □□□□

Yoast PHP □□□□ □□□ PHPCS □□□□□□□□□ Yoast PHP □□□□□□□ PHP □□□□□ YoastCS □□□□ WordPress □□□□ □□□□□□□□□□□□ WPCS □□□□□□□□□□□□□□□

1. □□□□□□□□□□□□□□□

```
// Yoast □□
if ( $foo == 'bar' ) {
  echo 'It is Yoast style!';
```

```
}

// □□□□
if ( 'bar' == $foo ) {
  echo 'Yoda style is how this looks';
}
```

2. □□□ `else` □□□□□

```
// Yoast □□□
if ( $foo == 'bar' ) {
  echo 'foo bar';
}
else {
  echo 'foo is not bar';
}

// WordPress □□□□□
if ( $foo == 'bar' ) {
  echo 'foo bar';
} else {
  echo 'foo is not bar';
}
```

JavaScript □□□□

□□□ [JavaScript □□□□]() □□□ ESLint □□□□□ JavaScript □ PHP □□□ ES6 □□□□□□ Webpack □ Babel □□□□□□□□□□□□□□□□

□□□□

□□□

- □□□□□□□□□□□ `www` □ `http` □ `SEO` □□□□□□□□□
- □□□□□□□□□□□□□□□□□□□□□□□ `needle` □ `haystack` □

- [illegible]

[illegible]

[illegible] KISS[illegible]

[illegible] KISS [illegible] S [illegible]

[illegible] DRY[illegible]

[illegible] DRY[illegible] DRY [illegible]

SOLID

SOLID [illegible]

[illegible] SOLID [illegible] S [illegible]

[illegible]

[illegible] Yoast[illegible] PHPUnit [illegible] PHP [illegible] Jest [illegible] JavaScript [illegible]

[illegible]

- [illegible]
- [illegible]

对于每个 PR，检查变更是否被单元测试覆盖。

测试驱动开发 (TDD)

TDD
是一种在编写实际实现代码之前先编写测试的原则。通过这种方式工作，你被迫提前思考要解决的问题。由于测试应该是独立且小巧的，你也已经在思考将要编写的实现功能的代码。虽然我们并不严格强制这种工作方式，但它是养成测试习惯的好方法。

代码侦察原则

重构应主要遵循代码侦察原则。这意味着你离开时留下的代码应比发现时更好。在修复错误或添加新功能时，
可以花些时间改进相关功能。当然，仅在确实需要时这样做，并记住保持简洁。

其他

尝试 /捕获 “随机 ”功能

某些功能具有随机的成功因素。例如：进行 API 调用时，你永远无法确定 API
是否可用。我们不希望软件因此中断。请将此类功能包装在 try/catch 块中。

压缩 .js 和 .css 文件
请确保你的 JS 和 CSS 文件已被压缩 /混淆，并在浏览器中加载压缩版本。我们的大多数仓库都配置了 Grunt
来帮你完成这项工作。只需运行 grunt build 即可！

PHPDocs 与注释

确保所有代码都使用 PHPDoc 进行文档化。必要时也使用行内注释，例如在描述复杂代码段时。

版本号 #2
由 壳壳虫 创建于 2026-03-26 17:08:40 UTC
由 壳壳虫 更新于 2026-03-26 17:08:40 UTC